



300mA Low Dropout Anti Back Irrigation CMOS Voltage Regulators

■ General Description

The LN1138 series are highly precise, low noise, positive voltage LDO regulators manufactured using CMOS processes. The series achieves high ripple rejection and low dropout and consists of a standard voltage source, an error correction, current limiter and a phase compensation circuit plus a driver transistor. Output voltage is selectable in 100mV increments within a range of 1.5V ~ 5.0V. The series is also compatible with low ESR ceramic capacitors which give added output stability. This stability can be maintained even during load fluctuations due to the excellent transient response of the series.

The current limiter's feedback circuit also operates as a short protect for the output current limiter and the output pin. The CE function enables the output to be turned off, resulting in greatly reduced power consumption.

■ Features

- Output Voltage Range: 1.0V to 5.0V (selectable in 100mV steps)
- Highly Accurate: $\pm 2\%$
- Dropout Voltage: 300mV @ 100mA (3.0V type)
- High Ripple Rejection: 70dB (10 kHz)

■ Ordering Information

LN1138 ①②③④⑤⑥

- Low Power Consumption: 20 μ A (TYP.)
- Maximum Output Current : 300mA ($V_{IN} \geq V_{OUT} + 1V$)
- Standby Current : less than 0.1 μ A
- Internal protector: current limiter ,short protector and anti back irrigation

■ Applications




- Mobile phones
- Cordless phones
- Cameras, Video cameras
- Portable games
- Portable AV equipment
- Reference voltage
- Battery powered equipment

■ Package

- SOT-353/SC70-5
- SOT-23-3
- SOT-23-5L
- USP-6B

Designator	Symbol	Description	Designator	Symbol	Description
①		CE Pin Logic :	⑤		Package Type :
	A	Active 'High' (pull-down resistor built in)		M	SOT-23-5L
	B	Active 'High' (no pull-down resistor built in)		K	SOT-353/SC70-5
	C	Active 'Low' (pull-up resistor built in)		D	USP-6B
	D	Active 'Low' (no pull-up resistor built in)		N	SOT-23-3
② ③	18-60	Output Voltage: e.g. 20 = 2.0V 30 = 3.0V etc.	⑥		Device Orientation :
④	2	Output Voltage : 100mV increments e.g. ②=3, ③=8, ④=2 \Rightarrow 3.8V		R	Embossed Tape : Standard Feed
	A	Output Voltage : 50mV increments e.g. ②=3, ③=8, ④=A \Rightarrow 3.85V		L	Embossed Tape : Reverse Feed

■ Pin Configuration





■ Pin Assignment

Pin Number				Pin Name	Function
SOT-23-5L	USP-6B	SOT-353/SC70-5	SOT-23-3		
1	1	1	1	VIN	Supply Power
2	5	2	3	VSS	Ground
3	6	3	-	CE	Enable Pin
4	2, 4	4	-	NC	Not Connctet
5	3	5	2	VOUT	Voltage Output

■ Marking Rule

- SOT-23-5,SOT-353,SOT-343(Top View)



- ① Represents the product name

Symbol	Product Name
4	LN1138◆◆◆◆◆◆

- ② Represents the range of output voltage

Voltage(V)	1.0~3.0	3.1~6.0	1.05~3.05	3.15~6.05		
Symbol	V	A	E	L	Product Name	LN1138A◆◆◆◆◆
	X	B	F	M		LN1138B◆◆◆◆◆
	Y	C	H	N		LN1138C◆◆◆◆◆
	Z	D	K	P		LN1138D◆◆◆◆◆



③ Represents the Output Voltage


Symbol	Output Voltage (V)			
0		3.1		3.15
1		3.2		3.25
2		3.3		3.35
3		3.4		3.45
4		3.5		3.55
5		3.6		3.65
6		3.7		3.75
7		3.8		3.85
8		3.9		3.95
9	1.0	4.0	1.05	4.05
A	1.1	4.1	1.15	4.15
B	1.2	4.2	1.25	4.25
C	1.3	4.3	1.35	4.35
D	1.4	4.4	1.45	4.45
E	1.5	4.5	1.55	4.55

Symbol	Output Voltage (V)			
F	1.6	4.6	1.65	4.65
H	1.7	4.7	1.75	4.75
K	1.8	4.8	1.85	4.85
L	1.9	4.9	1.95	4.95
M	2.0	5.0	2.05	5.05
N	2.1		2.15	
P	2.2		2.25	
R	2.3		2.35	
S	2.4		2.45	
T	2.5		2.55	
U	2.6		2.65	
V	2.7		2.75	
X	2.8		2.85	
Y	2.9		2.95	
Z	3.0		3.05	

④ Represents the assembly lot no.

0~9, A~Z repeated (G, I, J, O, Q, W excepted)

- USP-6B



USP-6B

① ② Represents the product name

Symbol		Product Name
①	②	
3	4	LN1138xxxxDx

③ Represents the type of regulator

Symbol	Type	Product Name
A	Active 'High' (pull-down resistor built in)	LN1138AxxxxDx
B	Active 'High' (no pull-down resistor built in)	LN1138BxxxxDx
C	Active 'Low' (pull-up resistor built in)	LN1138CxxxxDx
D	Active 'Low' (no pull-up resistor built in)	LN1138DxxxxDx



④ Represents the integers of Output Voltage

Example: 3 represents 3.x, 5 represents 5.x


⑤ Represents the decimals of Output Voltage

Symbol	Voltage (V)	Product Name	Symbol	Voltage (V)	Product Name
0	X.0	LN1138XX0XDX	A	X.05	LN1138XXAXDX
1	X.1	LN1138XX1XDX	B	X.15	LN1138XXBXDX
2	X.2	LN1138XX2XDX	C	X.25	LN1138XXCXDX
3	X.3	LN1138XX3XDX	D	X.35	LN1138XXDXDX
4	X.4	LN1138XX4XDX	E	X.45	LN1138XXEXDX
5	X.5	LN1138XX5XDX	F	X.55	LN1138XXFXDX
6	X.6	LN1138XX6XDX	H	X.65	LN1138XXHXDX
7	X.7	LN1138XX7XDX	K	X.75	LN1138XXKXDX
8	X.8	LN1138XX8XDX	L	X.85	LN1138XXLXDX
9	X.9	LN1138XX9XDX	M	X.95	LN1138XXMXDX

⑥ Represents the assembly lot No.

0~9, A~Z repeated (G, I, J, O, Q, W excepted)

■ Function Block Diagram






Absolute Maximum Ratings

Parameter	Symbol	Maximum Rating		Unit
Input Voltage	V _{IN}	V _{SS} -0.3~V _{SS} +8		V
	V _{ON/OFF}	V _{SS} -0.3~V _{IN} +0.3		
Output Current	V _{OUT}	V _{SS} -0.3~V _{IN} +0.3		
Power Dissipation	P _D	SOT-23-5,SOT-353/SC70-5	250	mW
		USP-6B	100	
Operating Ambient Temperature	Topr	-40~+85		°C
Storage Temperature	Tstg	-40~+125		

Caution: The absolute maximum ratings are rated values exceeding which the product could suffer physical damage. These values must therefore not be exceeded under any conditions.

Typical Application Circuit



Caution: The above connection diagram and constant will not guarantee successful operation. Perform thorough evaluation using the actual application to set the constant.


Application Conditions

Input capacitor (CIN): 1.0μF or more

Output capacitor (CL): 1.0μF or more (tantalum capacitor)

Caution A general series regulator may oscillate, depending on the external components selected. Check that no oscillation occurs with the application using the above capacitor.

Test Circuits






■ Electrical Characteristics

Parameter	Symbol	Condition	Min	Typ	Max	Unit	Circuit
Output Voltage	$V_{OUT(E)}$	$V_{IN}=V_{OUT(S)}+1.0\text{ V}$, $I_{OUT}=30\text{ mA}$	$V_{OUT(S)}\times 0.98$	$V_{OUT(S)}$	$V_{OUT(S)}\times 1.02$	V	1
Output Current	I_{OUT}	$V_{IN}\geq V_{OUT(S)}+1.0\text{ V}$	500	—	—	mA	1
Dropout Voltage	V_{drop}	$I_{OUT}=50\text{ mA}$	—	0.12	0.20	V	1
		$I_{OUT}=100\text{ mA}$	—	0.30	0.45		
Line Regulations	$\frac{\Delta V_{OUT1}}{\Delta V_{IN} \bullet V_{OUT}}$	$V_{OUT(S)}+0.5\text{ V} \leq V_{IN} \leq 8\text{ V}$ $I_{OUT}=30\text{ mA}$	—	0.10	0.2	%/V	
Load Regulation	ΔV_{OUT2}	$V_{IN}=V_{OUT(S)}+1.0\text{ V}$ $1.0\text{ mA} \leq I_{OUT} \leq 100\text{ mA}$	—	50	100	mV	
Output Voltage Temperature Characteristics	$\frac{\Delta V_{OUT}}{\Delta Ta \bullet V_{OUT}}$	$V_{IN}=V_{OUT(S)}+1.0\text{ V}$, $I_{OUT}=10\text{ mA}$ $-40^{\circ}\text{C} \leq Ta \leq 85^{\circ}\text{C}$	—	± 100	—	ppm/ $^{\circ}\text{C}$	
Supply Current	I_{SS1}	$V_{IN}=V_{OUT(S)}+1.0\text{ V}$	—	20	—	μA	2
Input Voltage	V_{IN}	—	2.0	—	8	V	—
Ripple-Rejection	PSRR	$V_{IN}=V_{OUT(S)}+1.0\text{ V}$, $f=10\text{ kHz}$ $V_{rip}=0.5\text{ Vrms}$, $I_{OUT}=50\text{ mA}$	—	70	—	dB	1
Short-circuit Current	I_{short}	$V_{IN}=V_{OUT(S)}+1.0\text{ V}$, V_{CE} on $V_{OUT}=\text{gnd}$	—	60	—	mA	1
CE "High" Voltage	V_{CEH}		1.6		V_{IN}	V	1
CE "Low" Voltage	V_{CEL}				0.25	V	1
CE "High" Current	I_{CEH}	$V_{IN}=V_{CE}=V_{OUT(T)}+1.0\text{ V}$	-0.1		0.1	μA	2
CE "Low" Current	I_{CEL}	$V_{IN}=V_{OUT(T)}+1.0\text{ V}$, $V_{CE}=V_{SS}$	-0.1		0.1	μA	2




■ Typical Performance Characteristics (3.0V output)


1、Output Voltage vs. Output Current




2、Output Voltage vs. Input Voltage (Contd.)




3、Dropout Voltage vs. Output Current




4、Dropout Voltage vs. Output Voltage




5、Output Voltage vs. Ambient Temperature



6、Ripple Rejection Rate




7、Anti back irrigation current






7、Transient Response

Input Transient Response




Load Transient Response





■ Package Information


- SOT-23-5L



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°




- SOT-353/SC70-5



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.150	0.350	0.006	0.014
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°




● SOT-23-3




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°




• USP-6B



Top View



Bottom View



Side View

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.700/0.800	0.800/0.900	0.028/0.031	0.031/0.035
A1	0.000	0.050	0.000	0.002
A3	0.203REF.		0.008REF.	
D	1.900	2.100	0.075	0.083
E	1.900	2.100	0.075	0.083
D1	1.100	1.300	0.043	0.051
E1	0.600	0.800	0.024	0.031
k	0.200MIN.		0.008MIN.	
b	0.180	0.300	0.007	0.012
e	0.650TYP.		0.026TYP.	
L	0.250	0.450	0.010	0.018