



## TGD N-Channel Enhancement Mode Power MOSFET

**Description**

The TGD8098 uses advanced trench technology and design to provide excellent  $R_{DS(ON)}$  with low gate charge. It can be used in a wide variety of applications.

**General Features**




- $V_{DS} = 80V, I_D = 98A$
- $R_{DS(ON)} < 8m\Omega @ V_{GS}=10V$  (Typ:6.5m $\Omega$ )
- High density cell design for ultra low  $R_{DS(on)}$
- Fully characterized avalanche voltage and current
- Good stability and uniformity with high  $E_{AS}$
- Excellent package for good heat dissipation
- Special process technology for high ESD capability

**Application**

- Power switching application
- Hard switched and high frequency circuits
- Uninterruptible power supply

**100% UIS TESTED!**

**100%  $\Delta V_{ds}$  TESTED!**

**Schematic diagram****pin assignment****TO-220-3L top view****Package Marking and Ordering Information**

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
TGD8098	TGD8098	TO-220	-	-	-

**Absolute Maximum Ratings ( $T_A=25^\circ C$  unless otherwise noted)**

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	$V_{DS}$	80	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Drain Current-Continuous	$I_D$	98	A
Drain Current-Continuous( $T_C=100^\circ C$ )	$I_D (100^\circ C)$	70	A
Pulsed Drain Current	$I_{DM}$	520	A
Maximum Power Dissipation	$P_D$	180	W
Derating factor		1.2	W/ $^\circ C$
Single pulse avalanche energy <small>(Note 5)</small>	$E_{AS}$	800	mJ
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 To 175	$^\circ C$

**Thermal Characteristic**

Thermal Resistance,Junction-to-Case <sup>(Note 2)</sup>	R <sub>θJC</sub>	0.83	°C/W
---------------------------------------------------------	------------------	------	------

**Electrical Characteristics ( $T_A=25^\circ\text{C}$  unless otherwise noted)**


Parameter	Symbol	Condition	Min	Typ	Max	Unit
<b>Off Characteristics</b>						
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	V <sub>GS</sub> =0V I <sub>D</sub> =250μA	80	86	-	V
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> =80V, V <sub>GS</sub> =0V	-	-	1	μA
Gate-Body Leakage Current	I <sub>GSS</sub>	V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V	-	-	±100	nA
<b>On Characteristics</b> <sup>(Note 3)</sup>						
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA	2	3	4	V
Drain-Source On-State Resistance	R <sub>DS(ON)</sub>	V <sub>GS</sub> =10V, I <sub>D</sub> =40A	-	6.5	8	mΩ
Forward Transconductance	g <sub>FS</sub>	V <sub>DS</sub> =25V, I <sub>D</sub> =40A	80	-	-	S
<b>Dynamic Characteristics</b> <sup>(Note4)</sup>						
Input Capacitance	C <sub>iss</sub>	V <sub>DS</sub> =25V, V <sub>GS</sub> =0V, F=1.0MHz	-	4900	-	PF
Output Capacitance	C <sub>oss</sub>		-	410	-	PF
Reverse Transfer Capacitance	C <sub>rss</sub>		-	315	-	PF
<b>Switching Characteristics</b> <sup>(Note 4)</sup>						
Turn-on Delay Time	t <sub>d(on)</sub>	VDD=30V, ID=2A, RL=15Ω, RG=2.5Ω, VGS=10V	-	20	-	nS
Turn-on Rise Time	t <sub>r</sub>		-	19	-	nS
Turn-Off Delay Time	t <sub>d(off)</sub>		-	70	-	nS
Turn-Off Fall Time	t <sub>f</sub>		-	30	-	nS
Total Gate Charge	Q <sub>g</sub>	ID=30A, VDD=30V, VGS=10V	-	125	-	nC
Gate-Source Charge	Q <sub>gs</sub>		-	24	-	nC
Gate-Drain Charge	Q <sub>gd</sub>		-	49	-	nC
<b>Drain-Source Diode Characteristics</b>						
Diode Forward Voltage <sup>(Note 3)</sup>	V <sub>SD</sub>	V <sub>GS</sub> =0V, I <sub>S</sub> =40A	-	0.85	1.2	V
Diode Forward Current <sup>(Note 2)</sup>	I <sub>S</sub>		-	-	98	A
Reverse Recovery Time	t <sub>rr</sub>	TJ = 25°C, IF = 40A di/dt = 100A/μs <sup>(Note3)</sup>	-	37	-	nS
Reverse Recovery Charge	Q <sub>rr</sub>		-	58	-	nC
Forward Turn-On Time	t <sub>on</sub>	Intrinsic turn-on time is negligible (turn-on is dominated by LS+LD)				

**Notes:**


1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, t ≤ 10 sec.
3. Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
4. Guaranteed by design, not subject to production
5. EAS condition: Tj=25°C, V<sub>DD</sub>=40V, V<sub>G</sub>=10V, L=0.5mH, Rg=25Ω

## Test circuit


### 1) E<sub>AS</sub> test Circuits




### 2) Gate charge test Circuit:




### 3) Switch Time Test Circuit:




### Typical Electrical and Thermal Characteristics (Curves)




**Figure 1 Output Characteristics**




**Figure 4 Rdson-JunctionTemperature**




**Figure 2 Transfer Characteristics**




**Figure 5 Gate Charge**




**Figure 3 Rdson- Drain Current**




**Figure 6 Source- Drain Diode Forward**




**Figure 7 Capacitance vs Vds**




**Figure 9 BV<sub>DSS</sub> vs Junction Temperature**



**Figure 8 Safe Operation Area**




**Figure 10 V<sub>GS(th)</sub> vs Junction Temperature**



**Figure 11 Normalized Maximum Transient Thermal Impedance**

## TO-220-3L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	4.400	4.600	0.173	0.181
A1	2.250	2.550	0.089	0.100
b	0.710	0.910	0.028	0.036
b1	1.170	1.370	0.046	0.054
c	0.330	0.650	0.013	0.026
c1	1.200	1.400	0.047	0.055
D	9.910	10.250	0.390	0.404
E	8.9500	9.750	0.352	0.384
E1	12.650	12.950	0.498	0.510
e	2.540 TYP.		0.100 TYP.	
e1	4.980	5.180	0.196	0.204
F	2.650	2.950	0.104	0.116
H	7.900	8.100	0.311	0.319
h	0.000	0.300	0.000	0.012
L	12.900	13.400	0.508	0.528
L1	2.850	3.250	0.112	0.128
V	7.500 REF.		0.295 REF.	
Φ	3.400	3.800	0.134	0.150